

FA0401

VALVOLA A SFERA IN OTTONE SERIE LEGGERA F/F CON LEVA IN ALLUMINIO
F/F BRASS BALL VALVE LIGHT SERIES WITH ALUMINIUM LEVER

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA0401-1/4	1/4	
FA0401-3/8	3/8	
FA0401-1/2	1/2	
FA0401-3/4	3/4	
FA0401-1	1	
FA0401-1-1/4	1" 1/4	
FA0401-1-1/2	1" 1/2	
FA0401-2	2	
FA0401-2-1/2	2" 1/2	
FA0401-3	3	
FA0401-4	4	

FA0301

VALVOLA A SFERA IN OTTONE SERIE PESANTE F/F CON LEVA IN ALLUMINIO
F/F BRASS BALL VALVE HEAVY SERIES WITH ALUMINIUM LEVER

Temperatura / Temperature: -20°C +130°C
Pressione / Pressure: da 40 a 80 bar / from 40 to 80 bar



FA0301-1/4	1/4	
FA0301-3/8	3/8	
FA0301-1/2	1/2	
FA0301-3/4	3/4	
FA0301-1	1	
FA0301-1-1/4	1" 1/4	
FA0301-1-1/2	1" 1/2	
FA0301-2	2	
FA0301-2-1/2	2" 1/2	
FA0301-3	3	

FA0402

VALVOLA A SFERA IN OTTONE SERIE LEGGERA M/F CON LEVA IN ALLUMINIO
M/F BRASS BALL VALVE LIGHT SERIES WITH ALUMINIUM LEVER

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA0402-1/4	1/4	
FA0402-3/8	3/8	
FA0402-1/2	1/2	
FA0402-3/4	3/4	
FA0402-1	1	
FA0402-1-1/4	1" 1/4	
FA0402-1-1/2	1" 1/2	
FA0402-2	2	
FA0402-2-1/2	2" 1/2	

FA0302

VALVOLA A SFERA IN OTTONE SERIE PESANTE M/F CON LEVA IN ALLUMINIO
M/F BRASS BALL VALVE HEAVY SERIES WITH ALUMINIUM LEVER

Temperatura / Temperature: -20°C +130°C
Pressione / Pressure: da 40 a 80 bar / from 40 to 80 bar



FA0302-1/4	1/4	
FA0302-3/8	3/8	
FA0302-1/2	1/2	
FA0302-3/4	3/4	
FA0302-1	1	
FA0302-1-1/4	1" 1/4	
FA0302-1-1/2	1" 1/2	
FA0302-2	2	

FA0421

VALVOLA A SFERA IN OTTONE SERIE LEGGERA F/F CON FARFALLA IN ALLUMINIO
F/F BRASS BALL VALVE LIGHT SERIES WITH ALUMINIUM THROTTLE

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA0421-1/4	1/4	
FA0421-3/8	3/8	
FA0421-1/2	1/2	
FA0421-3/4	3/4	
FA0421-1	1	

FA0321

VALVOLA A SFERA IN OTTONE SERIE PESANTE F/F CON FARFALLA IN ALLUMINIO
F/F BRASS BALL VALVE HEAVY SERIES WITH ALUMINIUM THROTTLE

Temperatura / Temperature: -20°C +130°C
Pressione / Pressure: da 40 a 80 bar / from 40 to 80 bar



FA0321-1/4	1/4	
FA0321-3/8	3/8	
FA0321-1/2	1/2	
FA0321-3/4	3/4	
FA0321-1	1	

FA0422

VALVOLA A SFERA IN OTTONE SERIE LEGGERA M/F CON FARFALLA IN ALLUMINIO
M/F BRASS BALL VALVE LIGHT SERIES WITH ALUMINIUM THROTTLE

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA0422-1/4	1/4	
FA0422-3/8	3/8	
FA0422-1/2	1/2	
FA0422-3/4	3/4	
FA0422-1	1	

FA0322

VALVOLA A SFERA IN OTTONE SERIE PESANTE M/F CON FARFALLA IN ALLUMINIO
M/F BRASS BALL VALVE HEAVY SERIES WITH ALUMINIUM THROTTLE

Temperatura / Temperature: -20°C +130°C
Pressione / Pressure: da 40 a 80 bar / from 40 to 80 bar



FA0322-1/4	1/4	
FA0322-3/8	3/8	
FA0322-1/2	1/2	
FA0322-3/4	3/4	
FA0322-1	1	

FA0123

VALVOLA A SFERA IN OTTONE SERIE PESANTE M/M CON FARFALLA IN ALLUMINIO
M/M BRASS BALL VALVE HEAVY SERIES WITH ALUMINIUM THROTTLE

Temperatura / Temperature: -20°C +130°C
Pressione / Pressure: da 40 a 80 bar / from 40 to 80 bar



FA0123-1/8	1/8	
FA0123-1/4	1/4	
FA0123-3/8	3/8	
FA0123-1/2	1/2	
FA0123-3/4	3/4	
FA0123-1	1	

FA0411

VALVOLA A SFERA IN OTTONE SERIE LEGGERA F/F CON LEVA IN ACCIAIO
F/F BRASS BALL VALVE LIGHT SERIES WITH STEEL LEVER

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA0411-1/4	1/4	
FA0411-3/8	3/8	
FA0411-1/2	1/2	
FA0411-3/4	3/4	
FA0411-1	1	

FA0412

VALVOLA A SFERA IN OTTONE SERIE LEGGERA M/F CON LEVA IN ACCIAIO
M/F BRASS BALL VALVE LIGHT SERIES WITH STEEL LEVER

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA0412-1/4	1/4	
FA0412-3/8	3/8	
FA0412-1/2	1/2	
FA0412-3/4	3/4	
FA0412-1	1	

FA0511

VALVOLA A SFERA IN OTTONE F/F CON LEVA LUCCHETTABILE
F/F BRASS BALL VALVE WITH LEVER FOR PADLOCK

Temperatura / Temperature: -15°C +120°C
Pressione / Pressure: da 40 a 63 bar / from 40 to 63 bar



FA0511-3/8	3/8	
FA0511-1/2	1/2	
FA0511-3/4	3/4	
FA0511-1	1	
FA0511-1-1/4	1" 1/4	
FA0511-1-1/2	1" 1/2	
FA0511-2	2	

FA2351

VALVOLA A SFERA IN OTTONE F/F CON FORO DI SCARICO E LEVA IN ALLUMINIO
F/F BRASS BALL VALVE WITH EXHAUST HOLE AND ALUMINIUM LEVER

Temperatura / Temperature: 0°C +60°C
Pressione / Pressure: max 12 bar



FA2351-1/4	1/4	
FA2351-3/8	3/8	
FA2351-1/2	1/2	
FA2351-3/4	3/4	
FA2351-1	1	
FA2351-1-1/4	1" 1/4	
FA2351-1-1/2	1" 1/2	
FA2351-2	2	

FA2070

VALVOLA A SFERA IN OTTONE SERIE LEGGERA F/F CON FARFALLA IN ALLUMINIO
F/F BRASS BALL VALVE LIGHT SERIES WITH ALUMINIUM THROTTLE

Temperatura / Temperature: -15°C +90°C
Pressione / Pressure: da 10 a 40 bar / from 10 to 40 bar



FA2070-1/2	1/2	
FA2070-3/4	3/4	
FA2070-1	1	