Line CONVEYOR-X

Disoleatore-silenziatore
Oil remover-silencer



Prodotto Product	∅ A	B	C	D	E	∅ F
CONVEYOR-X 25	61	ch.28	113	12	125	6
CONVEYOR-X 50	61	ch.40	161	12	173	6
CONVEYOR-X 150	86	ch.55	205	12	217	6

Caratteristiche Tecniche
Technical Features

Prodotto Product	Codice Code	Connessione Connection	Portata Flow Rates (0,7MPa/7Bar/100Psi		Peso Weght
			Nl/min	scfm	
CONVEYOR-X 25	D00.00.12025	1/2"	1500	53	0,10
CONVEYOR-X 50	D00.00.10050	1"	3000	105	0,14
CONVEYOR-X 150	D00.00.15150	1 !/2"	9000	315	0,37

Conveyor-X

Disoleatore/Silenziatore di scarico per sistemi pneumatici.
* Elimina l'inquinamento da nebbia d'olio prodotto dagli scarichi di valvole e cilindri.
* Riduce l'inquinamento acustico di 25 dBA riportando il livello del rumore a valori accettati dagli standard di sicurezza.
* Range di temperatura 2÷50°C (36÷122°F).
* Elemento filtrante in fibra di vetro coalescente.
* Tazza di raccolta olio con tappo di drenaggio.
* Possibilità di convogliare l'olio raccolto con un tubo ø6 mm.
* CONVEYOR - X é un dispositivo a perdere e va sostituito quando la contropressione diventa eccessiva.
* Prodotto conforme alla direttiva 2002/95/CE (RoHS).

Conveyor-X

Outlet Oil Remover/Silencer for pneumatic systems.
* Eliminate oil mist pollution produced by valve and cylinder outlets.
* Reduce acoustic pollution by 25 dBA, restoring noise levels to values accepted by the safety standards in force.
* Temperature range 2÷50°C (36÷122°C).
* Filtering element in coalescent glass fiber.
* Oil accumulating cup with drainage plug.
* The collected oil can be conveyed through a ø 6 mm pipe.
* CONVEYOR - X is disposable and should therefore be replaced when the over-pressure becomes excessive.
* Product complies with Directive 2002/95/CE (RoHS).